



US 20140337741A1

(19) **United States**(12) **Patent Application Publication**  
Reponen et al.(10) **Pub. No.: US 2014/0337741 A1**(43) **Pub. Date: Nov. 13, 2014**(54) **APPARATUS AND METHOD FOR AUDIO  
REACTIVE UI INFORMATION AND DISPLAY****Publication Classification**(71) Applicant: **Nokia Corporation**, Espoo (FI)(72) Inventors: **Erika Reponen**, Tampere (FI); **Ravi  
Shenoy**, Bangalore (IN); **Mikko Tammi**,  
Tampere (FI); **Sampo Vesa**, Helsinki (FI)(51) **Int. Cl.****G06F 3/16** (2006.01)**G06F 3/0484** (2006.01)**G06F 3/0481** (2006.01)(52) **U.S. Cl.**CPC ..... **G06F 3/167** (2013.01); **G06F 3/04817**  
(2013.01); **G06F 3/0484** (2013.01)USPC ..... **715/728**(73) Assignee: **Nokia Corporation**, Espoo (FI)(21) Appl. No.: **14/361,255**(22) PCT Filed: **Nov. 21, 2012**(86) PCT No.: **PCT/FI2012/051149**

§ 371 (c)(1),

(2), (4) Date: **May 28, 2014**(30) **Foreign Application Priority Data**

Nov. 30, 2011 (IN) ..... 4155/CHE/2011

(57)

**ABSTRACT**

A method includes determining, using signals captured from two or more microphones (1A) configured to detect an acoustic signal from one or more sound sources, one or more prominent sound sources based on the one or more sound sources (1C-1D). The method further includes determining one or more directions relative to a position of one or more of the two or more microphones for the one or more prominent sound sources (1B-1D). The method includes modifying one or more user interface elements displayed on a user interface of a display to provide an indication at least in part of the one or more directions, relative to position of at least one microphone, of the one or more prominent sound sources (1G).

